
>>> Type: WK 7,3 MA1 STG Steel cassette side walls (galvanized)

Dry Box with clinched side walls 7450 2550 Gesamthöhe 2750 Portalhöhe 2450 Eckhöhe 2725 185 600 0 0000 2259 ° min. 2590 ca. 4876 ca. 5523 798.5 798,5 5853

Rear view of container doors

v Box



Technical data	Standard	Option
Туре:	WK 7,3 MA1 STG	WK 7,7 MA1 STG
Perm. total weight:	16,000 kg	16,000 kg
Tare weight, approx.:	2,950 kg	3,050 kg
Internal length:	7,290 mm	7,660 mm
Internal width:	2,480 mm	2,480 mm
Total lenght:	7,450 mm	7,820 mm
Height of floor assembly, including floor:	185 mm	185 mm
Internal height:	2,530 mm	2,530 mm
Clear portal height:	2,450 mm	2,450 mm
Corner height:	2,725 mm	2,725 mm
Total height:	2,750 mm	2,750 mm
Landing height:	1,320 mm	1,320 mm
(Dimensions and weights for standard units)		

Technical description

185 mm high floor assembly incl. floor, with bottom guide tunnel; 4 container corner fittings on 20' base, symmetrical overhangs; 4 grapple bars; rear pull out ladder and retaining strap for rear access; horizontal steel collision protection on rear profile, left and right

4 laterally extendable/folding support legs, 2-fold secured; support legs with reflectors glued to the front (reflectors point forwards when parked); support leg lock can be operated from the outside

27 mm thick plywood floor, fully waterproofed and sealed, resistance test according to EN 283, for floor loadings up to 5.460 kg forklift axle load; 2 ventilation slots at front in the floor (according to GGVS)

Profiled roof with steel trapezium sheets, height: 25 mm

Closed superstructure; smooth side walls made of galvanised sheet steel cassettes; 2 ventilation vents per side wall; forklift collision protection inside, 3-sided, approx. 360 mm high

Profiled roof with steel trapezium sheets, height: 25 mm

Smooth front wall made of galvanised sheet steel cassettes; inside with wooden covering; lower panel as replaceable impact protection; front wall outside with offset at the top (optimised for driving around curves)

Rear wall as steel container door with replaceable seal (width in length approx. 2,470 mm); external door locks; door retainer as reinforced chain

Customs seal, customs plate

Steel parts are shot blasted, KTL primed with zinc phosphating and powder-coated; 1-colour standard paint finish; grappler pockets in contrasting colours in contrasting color; support legs in black



🗥 KRONE